



# COOK

# Shutter

DATE: \_\_\_\_\_

PROJECT: \_\_\_\_\_

LOCATION: \_\_\_\_\_

Discharge  
Galvanized Construction  
EWB, EWD, EPB, EPD  
Propeller Fans

### DIMENSION DATA

Model Number	Unit Size	A Sq.	B Sq.	Number of Panels	Shipping Wt.
GSG-33	24	36	33	1	20
GSG-39	30	42	39	1	26
GSG-45	36	48	45	2	33
GSG-51	42	54	51	2	40
GSG-57	48	60	57	2	49
GSG-63	54	66	63	2	56
GSG-69	60	72	69	4	67
GSG-81	72	84	81	8	93

ALL DIMENSIONS IN INCHES. WEIGHTS IN LBS.  
THE MODEL GSG SHUTTERS ARE DESIGNED TO REDUCE BACK DRAFTS; PREVENT ENTRY OF SOME FOREIGN MATERIAL AND PESTS, SUCH AS BIRDS; AND LIMIT THE AMOUNT OF RAIN THAT ENTERS THE BUILDING. THESE SHUTTERS ARE INTENDED TO BE WEATHER-RESISTANT, BUT ARE NOT WEATHER-PROOF FOR EXTREME CONDITIONS.

### STANDARD CONSTRUCTION FEATURES:

Galvanized steel blades and frame - Stainless steel pivots - Vinyl blade edge seals.

### NOTES:

- 1) TO ORDER A MOTORIZED SHUTTER, SUBSTITUTE "M" FOR FIRST "G" IN MODEL NO.
- 2) MOTORIZED MODELS 33-63 REQUIRE 1 MOTOR.
- 3) MOTORIZED MODEL 69 REQUIRE 2 MOTORS.
- 4) MOTORIZED MODEL 81 REQUIRE 4 MOTORS.
- 5) ADD 2# TO SHIPPING WEIGHT FOR EACH MOTOR ON MOTORIZED UNITS.
- 6) MOTOR OPERATED DAMPERS REQUIRED FOR VELOCITIES BELOW 600 FPM. MAXIMUM VELOCITY 3000 FPM.

