



COOK

FSC

DATE: _____

PROJECT: _____

LOCATION: _____

PRODUCT DESCRIPTION:

The Loren Cook Company speed control system incorporates the most advanced design on the market today. Through use of the "Quadrac" integrated semi-conductor device it is now possible to offer this system with many advantages. Fewer semi-conductor parts mean greater reliability and the passivation process used in the manufacture of the semi-conductor insures long life. Printed circuit construction eliminates wiring difficulties and guarantees workmanship. All of these factors serve to offer the most important of all features - quality.



Accessory Data Sheet Fan Speed Controls

SPEED CONTROL

Positive Off/On Action in the control dial. Speed range set to customer's requirements.

CONTROL RATING

120 volts, 60 cycles, 1 phase. Maximum Ambient Temperature - 120°F. (5 AMP, 10 AMP, 15 AMP)
220/240 volt, 50/60 cycles, 1 phase. Maximum Ambient Temperature - 120°F. (5 AMP, 10 AMP)
220/240 volt model not UL listed. Fan cannot have UL listing if furnished with prewired 220/240 volt FSC.
277 volts, 60 cycles, 1 phase. Maximum Ambient Temperature - 120°F. (5 AMP)

WARNING

Power must be turned off before installing this unit.

STANDARD INSTALLATION

Fits any standard single gang box. Turn off power and connect the two wires on the control to the two switch wires in the usual manner.

The connection box is not supplied.

SPECIAL FEATURES:

- Complete Range Control
- Solid State "Quadrac" Integrated Circuitry
- Solid State Construction for Long Reliable Operating Life
- Saves on Electric Bills

